



Model 9070 GENERAL DIMENSIONS

CRANE: HEIGHT

A ¹	Rails to Top of Gantry Sheaves (For Shipping)	15' 1-3/8"
A ²	Rails to Top of Gantry Sheaves (Working)	22' 4-5/8"
A ³	AAR Plate "C"	15' 1"
B	Rails to Top of Standard Operators Cab	16' 11-5/16"
	Rails to Top of 6'0" Operators Cab	22' 11-5/16"
C	Rails to Top of Machinery Cab	13' 9-1/4"
D	Rails to Boom Foot	7' 6-7/8"
E	Rails to Bottom of Upper Works	5' 6-1/8"

WIDTH

F ₁	For Travel	10' 10-7/16"
F ₂	Centerline to Outside of Operators Cab Door (Removed for Shipping)	6' 0-13/16"
G	Rotation Center to Boom Foot	5' 0-3/4"
H	Tailswing	15'

BOOM SECTION:

R	Boom Length	60' 0"
---	-------------	--------

CARBODY: HEIGHT

I	Rails to Top of Carbody	4' 4-1/8"
J	Rails to Center of Couplers	2' 9-1/2"
K	Rails to Bottom of Outriggers	1' 5-1/4"
L	Top of Carbody to Bottom of Upper Works	1' 2"

WIDTH

M	Centerline to Retracted Outrigger	5' 4-1/4"
N	Centerline to Fully Extended Outrigger	9' 3"

LENGTH

O	Coupler to Coupler	33' 2-1/2"
P	Center of Bolster to Center of Bolster	15' 0"
Q	Truck Wheel to Wheel	6' 8"

SHEAVES:

	DIA.
1	One Sheave 18"
2	Six Sheaves 18"
3	Five Sheaves 18"
4	Five Sheaves 30"